

PC Attachment 2

Table A-1: RS/DS Development Standards

	Single Family with Attached Sidewalk ⁴	Single Family with Separated Sidewalk ^{1, 4}
Lot Size (minimum)		
Area, Interior Lot	4,500 sq. ft.	4,275 sq. ft. ¹
Area, Corner Lot	5,500 sq. ft.	4,710 sq. ft. ¹
Width, Interior	45 ft.	45 ft.
Width, Corner	55 ft.	50 ft.
Permitted Density (maximum per lot)		
Residential Density	1 dwelling; 1 second unit	1 dwelling; 1 second unit
Setbacks (minimum)		
Front ²	15 ft. to living space or side wall of garage; 12.5 ft. to porch 18 ft. min. driveway depth	10 ft. to first-floor living space or side wall of garage 7.5 ft. to porch, but in no case may encroach into a PUE 15 ft. to second-floor living space 18 ft. min. driveway depth
Sides ²	Interior Lots: Corner Lots:	
	5 ft. 5 ft. interior side 12.5 ft. street side on first floor 15 ft. street side on second floor	5 ft. 5 ft. interior side 10 ft. street side on first floor 13 ft. street side on second floor
Rear	10 ft. minimum with minimum usable open space of 700 s.f. or 500 s.f. where a usable front porch is provided ³	10 ft. minimum with minimum usable open space of 500 s.f. ³
Coverage (maximum)		
Site Coverage	None ³	None ³
Height (maximum)		
Height	35 ft.	35 ft.
Supplemental Design Standards		
1. Front Yard Stagger	None required, but optional per unit design	
2. Stagger for 3 rd Car Garages	2 ft. between 3 rd car bay and two-car garage	
3. Two-story unit mix	No limit	
4. Separation Between Second Story Elements	A minimum of 10 feet shall be provided between second story elements of adjacent two-story dwellings	
5. Building Exterior	Architectural treatment shall be applied to all elevations of a building. At a minimum, all doors, windows and other wall openings shall be trimmed consistent with the architectural style. Panelized windows or other architectural treatment shall be used on all garage doors.	

- 1 Sidewalk separated from back of curb by 5-foot planter strip
- 2 Front setback (and side setback where adjacent to street) is measured from back of walk. Fence side yard setback is 5' from back of walk where facing a street. In the absence of a sidewalk, setback is measured from edge of right-of-way.
- 3 The rear and side yards may be utilized to meet the minimum usable open space provided the minimum dimension, measured perpendicular to the applicable rear or side yard is ten (10) feet. Maximum coverage is a function of lot size, required setbacks and usable open space. A minimum usable open space of 500 s.f. may be applied where a front porch is provided with minimum dimension of 6 ft. x 10 ft. exclusive of entry way.
4. Variations to the standards and other housing product types may be permitted subject to processing of a Design Review Permit for Residential Subdivisions (DRRS) concurrent with the approval of a tentative subdivision map and review of product type.