



NOTES:

1. SINGLE ENCLOSURE IS 12' WIDE (INTERIOR)
2. THE EXTERIOR FINISH AND COLOR OF THE ENCLOSURE SHALL MATCH THE BUILDING PER THE DESIGN REVIEW PERMIT EXHIBITS AND/OR CONDITIONS OF APPROVAL
3. GREASE/TALLOW BIN ENCLOSURE MAY BE ATTACHED TO THE TRASH ENCLOSURE OR BE CONSTRUCTED SEPARATELY. THE GREASE/TALLOW BIN MUST NOT BE LOCATED WITHIN THE TRASH/RECYCLING ENCLOSURE.
4. NO. 4 REBAR, 12 INCHES O.C. EACH WAY, 3 INCH DOBIES WITH WIRE TIES AT 3' INTERVALS, EACH WAY.



6' x 6"Ø CONC. FILLED BOLLARDS AT 3' O.C. (3' HIGH, 3' BURIED BELOW GROUND). SEE DETAIL ST-38A


SECTION A
BOLLARD CONFIGURATION



BOLLARD GATE
DETAIL

Richard D. Plecker

RICHARD PLECKER
ENVIRONMENTAL UTILITIES DIRECTOR



ENCLOSURE FLOOR TO BE POURED LEVEL

METAL GATE





ENVIRONMENTAL UTILITIES
DEPARTMENT

STANDARD TRASH ENCLOSURE

SCALE: NONE
REVISED: JANUARY 2025
DRAWN BY: J THOMPSON
APPROVED BY: RICHARD PLECKER


SW-1

REINFORCED CONCRETE APPROACH AND INTERIOR SHALL BE 6" THICK MIN. PAINTED "NO PARKING" 12" LETTERS WITH 4" DIAGONAL LINES






NOTES:

1. SINGLE ENCLOSURE IS 12' WIDE (INTERIOR)
2. THE EXTERIOR FINISH AND COLOR OF THE ENCLOSURE SHALL MATCH THE BUILDING PER THE DESIGN REVIEW PERMIT EXHIBITS AND/OR CONDITIONS OF APPROVAL
3. GREASE/TALLOW BIN ENCLOSURE MAY BE ATTACHED TO THE TRASH ENCLOSURE OR BE CONSTRUCTED SEPARATELY. THE GREASE/TALLOW BIN MUST NOT BE LOCATED WITHIN THE TRASH/RECYCLING ENCLOSURE.




6' x 6"Ø CONC. FILLED BOLLARDS AT 3' O.C. (3' HIGH, 3' BURIED BELOW GROUND). SEE DETAIL ST-38A




REINFORCED CONCRETE APPROACH AND INTERIOR SHALL BE 6" THICK MIN. PAINTED "NO PARKING" 12" LETTERS WITH 4" DIAGONAL LINES

Richard D. Plecker
 RICHARD PLECKER
 ENVIRONMENTAL UTILITIES DIRECTOR

	ENVIRONMENTAL UTILITIES DEPARTMENT
	FRONT LOADING COMPACTOR ENCLOSURE
SCALE: NONE REVISED: JANUARY 2025 DRAWN BY: J. THOMPSON APPROVED BY: RICHARD PLECKER	SW-2



PLAN
COMPACTOR BIN




PLAN
BIN & APPROACH

NOTES:


1. APPROACH SHALL BE 6" THICK REINFORCED CONCRETE SLAB ON GRADE. IT SHALL BE PAINTED "NO PARKING" IN 12" LETTERS AND STRIPED WITH 4" DIAGONAL LINES.
2. THE EXTERIOR FINISH AND COLOR OF THE ENCLOSURE SHALL MATCH THE BUILDING PER THE DESIGN REVIEW PERMIT EXHIBITS AND/OR CONDITIONS OF APPROVAL

Richard D. Plecker

RICHARD PLECKER
ENVIRONMENTAL UTILITIES DIRECTOR



FRONT



6" x 6" CONC. FILLED
BOLLARDS AT 3' O.C.
(3' HIGH, 3' BURIED
BELOW GROUND)

SECTION A
BOLLARD CONFIGURATION

ELEVATIONS




ENVIRONMENTAL UTILITIES
DEPARTMENT

**COMMERCIAL
COMPACTOR ENCLOSURE**

SCALE: NONE
REVISED: JANUARY 2025
DRAWN BY: R. VAN NESS
APPROVED BY: RICHARD PLECKER


SW-3



PLAN
COMPACTOR BIN

NOTES:


1. APPROACH SHALL BE 6" THICK REINFORCED CONCRETE SLAB ON GRADE. IT SHALL BE PAINTED "NO PARKING" IN 12" LETTERS AND STRIPED WITH 4" DIAGONAL LINES.
2. THE EXTERIOR FINISH AND COLOR OF THE ENCLOSURE SHALL MATCH THE BUILDING PER THE DESIGN REVIEW PERMIT EXHIBITS AND/OR CONDITIONS OF APPROVAL
3. IF GREASE/TALLOW BIN IS REQUIRED, SEE SW-1 AND SW-2 FOR DETAILS




SIDE

Richard D. Plecker

RICHARD PLECKER
ENVIRONMENTAL UTILITIES DIRECTOR



FRONT



6" x 6" Ø CONC. FILLED
BOLLARDS AT 3' O.C.
(3' HIGH, 3' BURIED
BELOW GROUND)

SECTION A
BOLLARD CONFIGURATION
(TRASH COMPACTOR)



ENVIRONMENTAL UTILITIES
DEPARTMENT

**RESIDENTIAL/COMMERCIAL
COMPACTOR ENCLOSURE**

SCALE: NONE
REVISED: APRIL 2022
DRAWN BY: D.SAMUELSON
APPROVED BY: RICHARD PLECKER

SW-4